

Axiohm A758 Thermal/Impact Hybrid Printer with Clamshell™ Receipt



Introducing the multifunction A758. Axiohm redefines convenience with the next generation of transaction printers!

The see through window on the check flip version means you will never lose sight of the check.



Axiohm™
Innovative Transaction Solutions

Fast Processing

At 40 lines per second thermal, and 4.8 lines per second impact, the A758 printer is the fastest in its class. What's more, the A758 includes an integrated MICR reader for fast and accurate check verification. You can save even more time with the optional check flip capability, allowing hands free printing on both sides of the check. This unique one-step check processing allows more time to be spent on customer service and speeding up the transaction.

High Volume Transactions

Use the A758 wherever you have high volume and need quick transaction processing for department, discount, specialty, grocery, and drug stores. In addition, the A758 comes with the Axiohm standards you have come to expect. Features such as the original Clamshell™ drop-in paper loading and the snap on ribbon cassette. Large standard flash memory allows you to print custom marketing messages, seasonal offers, special promotions and logos at a crisp 203 dots per inch.

Compatibility

Backwards compatible with the A756, the new Axiohm A758 automatically prints A756 graphics at the higher resolution of 203 DPI while maintaining exact proportions. The A758 also includes advanced features such as enhanced print modes, remote diagnostics, single button programming, and an expanded 90 mm paper capacity, the largest in its class.

Axiohm A758 Technical Specifications

	Receipt Station	Slip Station
Print Method	Direct Thermal, 203 DPI	9 Pin Impact
Character Cell Size	13 x 24, 10 x 24	7 x 7
CPI	15.6, 20.3	14, 17
Print Columns	44 & 56 columns	66 & 80
Print Line Width	2.8" (72mm)	4.75" (120mm)
Character Sets	Page 437, 850, 852, 858 (with Eurosymbol), 860, 863, 865, 866, user-defined. Contact your Axiohm representative for expanded character sets.	
Bar Codes	UPC-A, UPC-E, Code 39, Code 128, JAN8 and JAN13 (EAN), Interleaved 2 of 5, Codabar, PDF 417 (receipt station only)	
Printing Speed	40 LPS (130 mm/sec)	4.8 LPS (16 mm/sec)
Auto Cutter	Partial cut	
Data Buffer	4K	
User Memory	192K up to 1.7MB, shared for graphics, logos, user defined characters and user data storage.	
Communication Interface(s)	Mother/Daughter Board Architecture supports: RS- 232, IEEE 1284 Bi-Directional Parallel, USB	
Cash Drawer Control	1-2 Drawers	
MICR Reader	Integrated in slip station	
Character sets/fonts	E-13B and CMC-7, autodiscriminate	
Check read rate	99% minimum	
Parsing Formats	E-13B only. Programmable to any format	
Thermal Paper Requirements		
Paper Type	Direct Thermal, POS Grade(s)	
Paper Roll (W x Dia.)	3.15" x 3.55" (80 mm x 90 mm)	
Impact Slip Forms		
Size - Front insertion (L x W)	2.68" x 2.0" minimum (68 mm x 51 mm) 2.75" x 2.0" minimum with Flip Option (70 mm x 51 mm)	
Size - Side insertion (L x W)	2.0" x 8.0" minimum (51 mm x 204 mm)	
Number of Plies	1-5 ply multipart	
Paper Thickness	0.0160" maximum (0.400 mm)	
Power	24 VDC	
Certifications	EMI: FCC, ICES-003, VCCI: Class A; CE, Austel: Class B Safety: UL 1950, CSA 22.2 No.950, CE (EN60950), MITI (power supply)	
Reliability	Thermal Print Mechanism - 150KM paper (45M lines) Auto Knife Cutter - 1.5 M cuts Impact Print Mechanism - 15 M lines Impact Printhead - 200 M characters MICR reader - 200,000 Reads	
Dimensions (W x D x H)	9.0" x 10.4" x 7.0" (229 mm x 264 mm x 178 mm)	
Weight	Approx. 9.6 lbs. (4.4 kg)	
Control Language	EscPOS Compatible	
Options	Auto Knife Cutter MICR Reader with extended slip table Flip mechanism for one step check processing Extended Slip Table Kit Expanded flash memory	
Printer Drivers	OLE POS for Windows compatible and Windows/Windows NT Drivers	



For Information About Axiohm Products, Contact the Addresses Below or Visit our Website at www.axiohm.com

USA
950 Danby Road
Ithaca, NY 14850
Tel: (i) 800 732 8950
(i) 607 274 2500
Fax: (i) 607 274 2404

Manufacturing
860 Collegeview Dr.
Riverton, WY 82501
Tel: (i) 307 856 4821
Fax: (i) 307 856 0412

France - (33) 1 47 46 78 00
United Kingdom - (44) (0) 161 929 9933
Japan - (81) 338 629 880

Distributed by: